

Grandstand Attractions Inc.

2017 Super Stock Rules

Super Stock class is open to all men and women 16 and over. 16 and 17 year olds must have a notarized permit signed by parent/guardian. Driver must have a driver's license. In fairness to all, the following rules and regulations shall prevail.

PRIZE MONEY

Prize money is different at each show. Look at our schedule to find out prize money.

ENTRY FEE

Each car/driver shall pay \$40.00 unless otherwise posted. Each pit person shall pay \$20.00 unless otherwise posted. All drivers and pit persons must sign waiver and release of liability before entering pit area or track. Entries will be accepted up to 1 hour prior to show.

PARTICIPANT REGULATIONS

2003 and newer Vics must have stock cradle (No reinforcement of stock cradle). No jeeps, trucks (Rancheros and El Caminos are considered trucks), convertibles. No carryalls, Hearst, limos. No imperials or imperial sub frames allowed. NO LINCOLNS 61 to 70. Driver may maneuver forward or backward. No deliberate driver's door hits. If a driver does not hit another active car within one minute that car/driver shall be disqualified. No sandbagging, if you are sandbagging the race will be stopped and a sandbagger flag will be placed on your car. Cars must move when hit or show visible damage. Driver must remain in his/her car with helmet on until car is removed from track or officials tell you different. Make sure helmet strap is fastened. Helmet must remain worn during competition.

MANDATORY

You must have number on both doors big enough to read and bright enough color to see. Also must have number on roof with name on roof above front doors. Use your choice of number. If more than one of the same number shows up you may have to change your number. No profanity allowed on cars. Roof signs are accepted.

ENGINE

Any engine or transmission is allowed. Engines must be stock motor mounts. Lower engine cradle will be allowed (this is to only protect engine block). You may tie engines down using 2 chains, no more than 2 links of 3/8" chain welded to frame.

RADIATORS

Stock location only.

TRANSMISSION

Tranny coolers are allowed. No additional transmission protectors allowed.

BATTERY

Must be in a secure position and be covered with something nonflammable like rubber tube, rubber floor mat, etc. Batteries must be secured so they don't move. 2 12 volt batteries max.

REAR ENDS

Any 5 lug OEM car rear end may be ran. Car must have stock axles (no aftermarket axles allowed). One simple rear end brace, from backing plate, no wider than 3" x 3" allowed.

DRIVE SHAFTS

May be shortened or lengthened or you may use slip drive shaft.

SUSPENSION/ TRAILING ARMS & A-ARMS

No welding suspension parts what so ever. All must remain stock UNLESS STATED BELOW:

May be shortened or lengthened with no more than one inch overlap. No other reinforcement. A-arms may be bolted with one 5/8" bolt or nine wired (with 4 wraps), or one 3/8" chain (1 wrap), or can be welded with two 2" wide by 3" long straps. None of the above may be used as reinforcement. Spring spacers are allowed. Leaf springs must be stock thickness and width with 3" stagger in rear and 2" in front. You may add a maximum of 4 leaf spring clamps with a maximum material thickness of 1/4" and no wider than 1 1/2".

STEERING COLUMN/BRAKES/SHIFTER/GAS PEDAL

The steering column may be modified from box to steering wheel.

Brakes must be in stock location.

Aftermarket floor shifter and gas pedal are allowed.

HOOD/CORE SUPPORT

Hood must remain in factory position. 6 hood bolts allowed only the 2 core support bolts may go through the frame outside of radiator, in factory location. Bolts must not be any bigger than 1" with washers no bigger than 6" outside diameter. You must have 2 holes cut in the hood big enough for fire extinguisher, not directly over carburetor. You may use 20 bolts around header holes no bigger than SAE 3/8" with washers no bigger than 1" outside diameter.

TRUNK

You can use four 3/4" bolts in trunk and 2 may go through frame with washers no bigger than 6 inches outside diameter. Trunk lids must remain on factory hinges. Tucking or V'ing of trunk lid is allowed, but absolutely no wedging. You may chain or nine wire. NO MORE THAN 50% OF TRUCK MAY BE TUCKED. You may also weld trunk lid 5" leave 5" with 2" x 1/4" strap. Or bolt with 12 3/8" bolts. Creasing allowed but cannot be double creased.

BODY

No seam welding, no patching. Pre-denting and creasing are allowed (no DOUBLE CREASING).

FENDERS & QUARTER PANELS

Fenders may be trimmed and 10 bolts may be used per fender. Bolts are to be no bigger than 3/8" with washers no bigger than 1" outside diameter. Fenders may be trimmed, bolted or welded (with weld 1" skip 1"). Quarter panels must remain vertical within 3" of OEM position.

Grandstand Attractions Inc.

2017 Super Stock Rules

BODY MOUNT BOLTS

May be replaced with up to 3/4" bolts. All bolts must be inside frame with maximum washer size of 3".

FRAME

THE ONLY FRAME WELDING ACCEPTED IS AS FOLLOWS:

Front side of A-arms forward, top seam only, 1/2" wide weld. No added metal allowed. 12" maximum behind A-arms. Tilting will be allowed using weld rules as mentioned above.

FRAME REPAIRS

Four plates (4"x 5") will be allowed as repair plates. These are only repair plates and must be visually necessary repairs only. ALL DAMAGE MUST BE VISIBLE. NO EXCEPTIONS.

DOORS

Driver's door may be welded solid with a strap no bigger than 3", on the outside only. All other doors you may weld 5" on 5" off with strap no bigger than 3". Or you may chain or wire doors shut. NO WELDING ON WAGON TAILGATES. You may chain, nine wire or bolt in four places.

CAGE

You may have a cage with two side bars and three cross bars. The cage cannot extend past the dash area in the front and must be no further back than 2 inches in front of inner fender wells in the back. This can be welded in. Absolutely no kickers. You may have a halo bar. Must be vertical and within 12 inches of driver's seat. None of the cage or halo can connect to the frame. Halo cannot connect to the windshield bars or the roof sign. No gas tank protectors. Cage must be a minimum of 8" off floor and no higher than bottom of door windows.

BUMPERS

Must start with a factory bumper. May reinforce the inside of bumper but must remain stock. Bumpers may be reinforced no wider than frame rails. OUTSIDE OF BUMPERS MUST BE STOCK. Must have hole in the end of the bumper. Bumpers can only be reinforced between front bumper skin and stock backing. NO homemade pointy's. No reconfiguration of stock bumpers. Bumpers must be mounted in front of core support bolts. All bumpers and brackets must be passenger car origin, No rear brackets on front. All brackets and shocks must be mounted outside of frame unless factory shocks were mounted inside of frame (example 80's Ford). Cadillac and Y frame Chryslers must be mounted outside of frame. Bumpers and brackets may be welded solid to frame. NO brackets may extend further back than 10" from core support bolt. (DO NOT MOVE, RESHAPE OR REALIGN CORE SUPPORT BOLT HOLES) You may run 2 additional 4"x8"x1/4" straps per bumper and may be welded to frame to hold bumper. Bumper height from ground limited to 16" minimum with 22" maximum from bottom of bumper. For front of cars you must use front bumper brackets. No rear brackets on front (OEM). ANYTHING EXCESSIVE WILL NOT BE ALLOWED. IF YOU HAVE A QUESTION CALL PRIOR TO EVENT.

GAS TANKS

Maximum tank size is 7 gallons of gas. Fuel cells/metal boat tanks must be placed in back seat area and properly secured. NO STOCK TANKS. Fuel cells must be secured so there is no movement (do not use bungee cords for this). If tank is not secure you will not be running. Fuel cells must have secure caps and be leak proof. All fuel lines must have no leaks. Stock gas tanks must be removed or have holes in them and washed out. NO PLASTIC TANKS (heavy plastic racing fuel cells may be used). You must have a shield of metal or tin between driver and gas tank (this may be mounted with screws).

TIRES/RIMS

Tire inside of tire is allowed. Fork lift tires okay. No fluid inside of tires. Valve stem protectors are allowed. No reinforcing of rims except around bolt holes (2" maximum on outside diameter of lug holes).

9 WIRE

Unlimited amount may be used (PLEASE CALL WITH QUESTIONS).

SAFETY RULES AND REGULATIONS

1. Cars must have at least one bar attached from roof down to dash area to prevent hood from coming in.
2. Radiator overflow hose must be pointed at the ground and fastened so they cannot shoot water towards officials or other drivers.
3. Header pipes must be pointing straight up, cannot be aimed towards front of car.
4. NOTE: if you have a hole in the firewall it should be covered.
5. Safety belts required.
6. D.O.T. approved helmets mandatory. Any driver using an open faced helmet will not be covered by insurance if facial injury occurs.
7. Safety glasses or shield recommended.
8. Mandatory: you must wear long pants and a shirt. Fire suit recommended.
9. 2 fires and you are out unless it's a fuel fire then it's just 1 fire and you are out.
10. No alcoholic beverages or drugs allowed in pit area or on the track.
11. NO PIT PERSONS ALLOWED ON THE TRACK.
12. NOTE: Management does have the right to disqualify a car/driver at any time. Any person on track or causing trouble and not complying with the rules will be asked to leave (we can have you escorted off or have you arrested and you can be banned from running or being in pit area at future G.S.A. events).
13. Protests must be made no later than 5 minutes after the heat in question. No protests will be taken after the feature event. Only DRIVERS are allowed to protest a car. Officials will re-inspect the top cars.

These rules are for SUPER STOCK class and will remain SUPER STOCK class. DO NOT do any more than what is stated in these rules. Do not do anything to make your car illegal after inspection. If this happens you will be disqualified and no return of entry. Officials have the right to re-inspect your cars at any time. THIS IS THE MAXIMUM ALLOWANCE OF WHAT YOU CAN DO IN THIS CLASS.